

Minor Defects	Major Defects
AIR BRAKE SYSTEM	
1.1) audible air leak. 1.2) slow air pressure build-up rate.	1.3M) pushrod stroke of any brake exceeds the adjustment limit. 1.4M) air loss rate exceeds prescribed limit. 1.5M) inoperative towing vehicle (tractor) protection system. 1.6M) low air warning system fails or system is activated. 1.7M) inoperative service, parking or emergency brake.
CAB	
2.1) occupant compartment door fails to open.	2.2M) Any cab or sleeper door fails to close securely.
CARGO SECUREMENT	
3.1) insecure or improper load covering.	3.2M) insecure cargo. 3.3M) absence, failure, malfunction or deterioration of required cargo securement device or load covering.
COUPLING DEVICES	
4.1) coupler or mounting has loose or missing fastener.	4.2M) coupler is insecure or movement exceeds prescribed limit. 4.3M) coupling or locking mechanism is damaged or fails to lock. 4.4M) defective, incorrect, or missing safety chain or cable.
DANGEROUS GOODS	
-	5.1M) dangerous goods requirements not met.
DRIVER CONTROLS	
6.1) accelerator pedal, clutch, gauges, audible and visual indicators, or instruments fail to function properly.	-
DRIVER SEAT	
7.1) seat is damaged or fails to remain in set position.	7.2M) seatbelt or tether belt is insecure, missing or malfunctions.
ELECTRIC BRAKE SYSTEM	
8.1) loose or insecure wiring or electrical connection.	8.2M) inoperative breakaway device. 8.3M) inoperative brake.
EMERGENCY EQUIPMENT & SAFETY DEVICES	
9.1) emergency equipment is missing, damaged or defective.	-
EXHAUST SYSTEM	
10.1) exhaust leak, except as described as Major Defect.	10.2M) leak that causes exhaust gas to enter the occupant compartment.
FRAME & CARGO BODY	
11.1) damaged frame or cargo body.	11.2M) visibly shifted, cracked, collapsing or sagging frame member.
FUEL SYSTEM	
12.1) missing fuel tank cap.	12.2M) insecure fuel tank. 12.3M) dripping fuel leak.
GENERAL	
-	13.1M) serious damage or deterioration that is noticeable and may affect the vehicle's safe operation.

GLASS & MIRRORS	
14.1) required mirror or window glass fails to provide the required view to the driver as a result of being cracked, broken, damaged, missing or maladjusted. 14.2) required mirror or glass has broken or damaged attachments onto vehicle body.	-
COUPLING DEVICES	
15.1) control or system failure.	15.2M) defroster fails to provide unobstructed view through the windshield.
HORN	
16.1) vehicle has no operative horn.	-
HYDRAULIC BRAKE SYSTEM	
17.1) brake fluid level is below indicated minimum level.	17.2M) brake boost or power assist is not operative. 17.3M) brake fluid leak. 17.4M) brake pedal fade or insufficient brake pedal reserve. 17.5M) activated (other than ABS) warning device. 17.6M) brake fluid reservoir is less than ¼ full. 17.7M) parking brake is inoperative.
LAMPS	
18.1) required lamp does not function as intended. 18.2) required reflector is missing or partially missing.	When use of lamps is required: 18.3M) failure of both low-beam headlamps. 18.4M) failure of both rearmost tail lamps. At all times: 18.5M) failure of a rearmost turn-indicator lamp. 18.6M) failure of both rearmost brake lamps.
STEERING	
19.1) steering wheel lash (free-play) is greater than normal.	19.2M) steering wheel is insecure, or does not respond normally. 19.3M) steering wheel lash (free-play) exceeds prescribed limit.
SUSPENSION	
20.1) air leak in air suspension system. 20.2) a broken spring leaf. 20.3) suspension fastener is loose, missing, or broken.	20.4M) damaged (patched, cut, bruised, cracked to braid or deflated) air bag or insecurely mounted air bag. 20.5M) cracked or broken main spring leaf or more than one broken spring leaf in any spring assembly. 20.6M) part of spring leaf or suspension is missing, shifted out of place or is in contact with another vehicle component. 20.7M) loose U-bolt.
TIRES	
21.1) damaged tread or sidewall of tire. 21.2) tire leaking, if leak cannot be heard.	21.3M) flat tire. 21.4M) tire leaking, if leak can be felt or heard. 21.5M) tire tread depth is less than wear limit. 21.6M) tire is in contact with another tire or any vehicle component other than mudflap. 21.7M) tire is marked "Not for highway use". 21.8M) tire has exposed cords in the tread or outer sidewall area.
WHEELS/BEARINGS	
22.1) hub oil below minimum level (when fitted with sight glass). 22.2) leaking wheel seal.	22.3M) wheel has loose, missing or ineffective fastener. 22.4M) damaged, cracked or broken wheel, rim or attaching part. 22.5M) evidence of imminent wheel, hub or bearing failure.
WINDSHIELD WIPER/WASHER	
23.1) control or system malfunction. 23.2) wiper blade is damaged, missing or fails to adequately clear driver's field of vision.	When use of wipers or washer is required: 23.3M) wiper or washer fails to adequately clear driver's field of vision in area swept by driver's side wiper.
OTHER	
50) Other Minor Defects	50M) Other Major Defects